



# Likao Bearing Co., Ltd.



6207lu Bearing 2D drawings and 3D CAD models

35,000 mm x 72,000 mm x 17,000 mm ntn  
6207lu bearing

Bearing No. 6207lu

Size	35x72x17 mm
Bore Diameter	35,000 mm
Outer Diameter	72,000 mm
Width	17,000 mm
d	35,000 mm
D	72,000 mm
B	17,000 mm
C	17,000 mm
rs min	1.1 mm
Radial clearance class	CN
Mass	0.29 kg
Dynamic load, C	25.7 kN
Static load, C0	15.3 kN
Fatigue limit load, Cu	0.7 kN
f0	13.8
Nlim (grease)	6,300 rpm
Min operating temperature, Tmin	-25 ° C
Max operating temperature, Tmax	110 ° C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.61 Hz
Characteristic outer ring frequency, BPF0	3.56 Hz
Characteristic inner ring	5.44 Hz



## Likao Bearing Co., Ltd.

frequency, BPFI	
da min	41.5 mm
da max	45 mm
Da max	65.5 mm
ra max	1 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.29
EAN	4547359361223
Product Group	B00308
Enclosure	1 Seal
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C3-Loose
Inch - Metric	Metric
Long Description	35MM Bore; 72MM Outside Diameter; 17MM Outer Race Diameter; 1 Seal; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing



## Likao Bearing Co., Ltd.

Keyword String	Ball
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	6207LU
Weight / LBS	0.635
Bore	1.378 Inch   35 Millimeter
Outer Race Width	0.669 Inch   17 Millimeter
Outside Diameter	2.835 Inch   72 Millimeter
bore diameter:	35 mm
precision rating:	ISO Class 0
outside diameter:	72 mm
finish/coating:	Uncoated
overall width:	17 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Single Seal
inner ring width:	17 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	17 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	6300 rpm
internal clearance:	CN
fillet radius:	1.1 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	11000 RPM
dynamic load capacity:	25700 N
series:	62
static load capacity:	15300 N
manufacturer product page:	<a href="#">Click here</a>